

Tiras Sólidas		
Código	A(mm)	B(mm)
PN-7131	1,0	45,0
PN-7539	1,6	13,0
PN-8010	1,7	3,0
PN-0833	1,7	66,0
PN-3329	2,0	2,0
PN-8038	2,0	4,0
PN-0367	2,0	5,0
PN-8011	2,0	35,0
PN-7729	2,0	38,0
PN-0371	2,0	48,0
PN-7612	2,0	75,0
PN-7168	2,5	4,5
PN-0078	2,5	60,0
PN-7572	3,0	3,0
PN-7781	3,0	6,0
PN-0742	3,0	8,0
PN-0811	3,0	20,0
PN-0429	3,0	25,0
PN-7162	3,0	30,0
PN-7162	3,0	32,0
PN-7652	3,0	38,0
PN-0778	3,0	50,0
PN-7957	3,0	55,0
NH-006A	3,0	65,0
PN-7612	3,0	75,0
PN-0799	3,2	20,0
PN-7208	3,2	25,0
PN-7162	3,2	30,0
PN-7207	3,2	40,0
PN-0547	3,2	60,0
PN-8009	3,4	4,0
PN-8030	3,5	5,0
PN-0863	3,5	73,0
PN-8100	4,0	7,0
PN-7006	4,0	9,0
PN-7730	4,0	38,0
PN-8134	4,0	50,0
PN-7612	4,0	75,0
PN-7617	4,5	5,8
PN-7458	5,0	5,0
PN-0591	5,0	8,0
PN-0672	5,0	10,0
PN-7735	5,0	15,0
PN-7163	5,0	19,0
PN-7746	5,0	20,0

Tiras sólidas em SBR/Neoprene/NBR/EPDM cor: preta

Silicone colorido/transp. e preto.

Dureza 65 ± 5 sh A

Tiras Sólidas		
Código	A(mm)	B(mm)
PN-7025	5,0	30,0
PN-8001	5,0	35,0
PN-1027	5,0	50,0
PN-7612	5,0	75,0
PN-0873	6,0	6,0
PN-0762	6,0	9,3
PN-8041	6,0	30,0
PN-8088	6,0	50,0
PN-8119	6,0	70,0
PN-7612	6,0	75,0
PN-7883	6,4	76,2
PN-7091	6,5	6,5
PN-7327	6,5	50,0
PN-0979	7,0	22,0
PN-7997	7,0	40,0
PN-7998	7,0	50,0
PN-7076	8,0	8,0
PN-7918	8,0	10,0
PN-7221	8,0	20,0
PN-7648	8,0	30,0
PN-7328	8,0	50,0
PN-0726	8,5	8,5
PN-0719	9,0	9,0
PN-7406	9,5	9,5
PN-7164	9,5	19,0
PN-0719	10,0	10,0
PN-0834	10,0	15,0
PN-7302	10,0	16,0
PN-0911	10,0	24,0
PN-7527	10,0	25,0
PN-8067	10,0	30,0
PN-7193	10,0	40,0
PN-8112	10,0	50,0
PN-0761	11,0	17,0
PN-0912	12,0	12,0
PN-7564	12,0	30,0
PN-0648	12,0	32,0
PN-7509	12,0	70,0
PN-0661	12,5	12,5
PN-7225	13,0	13,0
PN-0929	13,0	16,0
PN-7222	13,0	20,0
PN-7885	13,0	22,0
PN-7165	13,0	25,0
PN-7165	13,0	25,0

Tiras sólidas em SBR/Neoprene/NBR/EPDM cor: preta

Silicone colorido/transp. e preto.

Dureza 65 ± 5 sh A

Tiras Sólidas		
Código	A(mm)	B(mm)
PN-7167	14,0	14,0
PN-7631	15,0	15,0
PN-7646	15,0	20,0
PN-7541	15,0	30,0
PN-7520	16,0	16,0
PN-7074	16,0	19,0
PN-8111	16,0	20,0
PN-7470	16,0	25,0
PN-8091	16,0	72,0
PN-7962	17,0	20,0
PN-0835	17,0	40,0
PN-7226	19,0	19,0
PN-7723	19,0	22,0
PN-7166	19,0	25,0
PN-7220	20,0	20,0
PN-7488	20,0	25,0
PN-7264	20,0	30,0
PN-8135	20,0	40,0
PN-8060	20,0	50,0
PN-7042	20,0	60,0
PN-7732	22,0	22,0
PN-7931	22,0	35,0
PN-7206	25,0	25,0
PN-7289	25,0	32,0
PN-0964	25,0	40,0
PN-7526	25,0	60,0
PN-7121	25,5	32,5
PN-8116	28,0	35,0
PN-7969	28,0	50,0
PN-8039	30,0	30,0
PN-7825	30,0	38,0
PN-0321	32,0	52,0
PN-8012	35,0	40,0
PN-8013	40,0	40,0
PN-7991	40,0	50,0
PN-0862	40,0	70,0
PN-0963	42,0	50,0

Tiras sólidas em SBR/Neoprene/NBR/EPDM cor: preta

Silicone colorido/transp. e preto.

Dureza 65 ± 5 sh A